Version 2.3

Revision Date 10/01/2023

Print Date 05/16/2024

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP DRY MOLY NC AERO DZ

Material number : 10601C

Manufacturer or supplier's	deta	ails
Company	:	Zep Inc.
Address	:	11627 - 178 Street Edmonton, Alberta T5S 1N6 Canada
Telephone	:	Compliance Services - 877-428-9937

Emergency telephone nu	mbe	rs
For SDS Information	:	Compliance Services - 877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency	:	CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

## SECTION 2. HAZARDS IDENTIFICATION

#### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	black
Odour	solvent-like

#### **GHS Classification**

Flammable aerosols Gases under pressure Eye irritation Specific target organ toxicity - single exposure	: Category 1 : Liquefied gas : Category 2A : Category 3 (Central nervous system)
GHS label elements	
Hazard pictograms	Flame
Signal word	: Danger

Version 2.3	Revision Date 10/01/2023	Print Date 05/16/2024
Hazard statements	<ul> <li>H222 Extremely flammable aero H280 Contains gas under presso H319 Causes serious eye irritatio H336 May cause drowsiness or</li> </ul>	ure; may explode if heated. on.
Precautionary statements	<ul> <li>Prevention:</li> <li>P210 Keep away from heat, hot and other ignition sources. No su P211 Do not spray on an open ff P251 Pressurized container: Do use.</li> <li>P261 Avoid breathing dust/ fume P264 Wash skin thoroughly after P271 Use only outdoors or in a v P280 Wear eye protection/ face <b>Response:</b></li> <li>P304 + P340 + P312 IF INHALE and keep comfortable for breathin CENTER/doctor if you feel unwe P305 + P351 + P338 IF IN EYES for several minutes. Remove cor easy to do. Continue rinsing.</li> <li>P337 + P313 If eye irritation pers attention.</li> <li><b>Storage:</b></li> <li>P403 + P233 Store in a well-vent tightly closed.</li> <li>P410 + P412 Protect from sunlig temperatures exceeding 50 °C/ <b>Disposal:</b></li> <li>P501 Dispose of contents/contait regulation.</li> </ul>	<ul> <li>moking.</li> <li>lame or other ignition source.</li> <li>not pierce or burn, even after</li> <li>a/ gas/ mist/ vapours/ spray.</li> <li>r handling.</li> <li>well-ventilated area.</li> <li>protection.</li> <li>D: Remove person to fresh air</li> <li>ng. Call a POISON</li> <li>II.</li> <li>S: Rinse cautiously with water</li> <li>ntact lenses, if present and</li> <li>sists: Get medical advice/</li> <li>tilated place. Keep container</li> <li>ght. Do not expose to</li> <li>122 °F.</li> </ul>

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
propan-2-ol	67-63-0	>= 60 - < 80
propane	74-98-6	>= 10 - < 30
butane	106-97-8	>= 10 - < 30

### **SECTION 4. FIRST AID MEASURES**

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical

rsion 2.3		Revision Date 10/01/2023	Print Date 05/16/2024
		advice.	
In case of skin contact	:	Wash off immediately with plenty minutes. If skin irritation persists, call a phy Remove contaminated clothing an Wash contaminated clothing befor	sician. Id shoes.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. Rinse immediately with plenty of v for at least 15 minutes. Protect unharmed eye. If eye irritation persists, consult a	vater, also under the eyelids
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to a If symptoms persist, call a physicia DO NOT induce vomiting unless of physician or poison control center	an. lirected to do so by a
Most important symptoms and effects, both acute and delayed	:	Effects are immediate and delayed Symptoms may include irritation, r Symptoms of overexposure may in dizziness; and confusion. May pro- paralysis, and convulsions.	edness, pain, and rash. nclude disorientation;
		Effects are dependent on exposur contact time). Causes serious eye irritation. May cause drowsiness or dizzines Review section 2 of SDS to see a	SS.
Notes to physician	:	Treat symptomatically. Symptoms	s may be delayed.

## SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: For safety reasons in case of fire, cans should be stored separately in closed containments.

Version 2.3	Revision Date 10/01/2023	Print Date 05/16/2024
	Use a water spray to cool fully clos	ed containers.
Special protective equipment for firefighters	: Wear self-contained breathing approximation approximatio	aratus for firefighting if

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<ul> <li>Do not breathe vapours or spray mist.</li> <li>Avoid exposure - obtain special instructions before use.</li> <li>Avoid contact with skin and eyes.</li> <li>For personal protection see section 8.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Take precautionary measures against static discharges.</li> <li>Provide sufficient air exchange and/or exhaust in work rooms.</li> <li>Always replace cap after use.</li> <li>Dispose of rinse water in accordance with local and national regulations.</li> </ul>
Conditions for safe storage	<ul> <li>BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.</li> <li>No smoking.</li> <li>Observe label precautions.</li> <li>Electrical installations / working materials must comply with the technological safety standards.</li> </ul>
Materials to avoid	Do not store near acids. Oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Version 2.3

#### Revision Date 10/01/2023

Print Date 05/16/2024

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH

## **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

# Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection		
Material	:	Protective gloves
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Safety glasses Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Version 2.3	Revision Date 10/01/2023	Print Date 05/16/2024
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and a	t the end of workday.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Colour: blackOdour: solvent-likeOdour Threshold: No data availablepH: Not applicable
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : No data available
Boiling point : No data available
Flash point :
No data available
Evaporation rate : No data available
Flammability (solid, gas, : Extremely flammable aerosol. liquid)
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : not determined
Density : 0.8 g/cm3
Solubility(ies)
Water solubility : insoluble
Partition coefficient: n- : No data available octanol/water
Auto-ignition temperature : not determined
Thermal decomposition : No data available
Viscosity
Viscosity, kinematic : No data available
Heat of combustion : 38.00 kJ/g

Version 2.3

 Revision Date 10/01/2023
 Print Date 05/16/2024

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents Acids
Hazardous decomposition products	: Carbon dioxide (CO2) Carbon monoxide Organic Substances

## SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects Aggravated Medical Condition	: None known.	
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pair Symptoms of overexposure may include disor dizziness; and confusion. May progress to un paralysis, and convulsions.	ientation;
	Effects are dependent on exposure (dose, cor contact time). Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential h Treat symptomatically. Symptoms may be de	azards.
Carcinogenicity:		
IARC	No component of this product present at levels g equal to 0.1% is identified as probable, possible human carcinogen by IARC.	
ACGIH	Confirmed animal carcinogen with unknown releven humans	ance to
	2-butoxyethanol	111-76-2
	Solvent naphtha (petroleum), light arom.	64742-95-6
	ethanol	64-17-5

Version 2.3

Print Date 05/16/2024

Product:

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

### **Components:**

## propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg Method: Calculation method

#### Skin corrosion/irritation

### Product:

Remarks: Irritating to skin.

#### Serious eye damage/eye irritation

### Product:

Remarks: Severe eye irritation

### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

### STOT - single exposure

## Product:

Exposure routes: Inhalation Assessment: May cause drowsiness or dizziness.

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### **Further information**

## Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic

Version 2.3

Revision Date 10/01/2023

Print Date 05/16/2024

effects., Solvents may degrease the skin.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

# Persistence and degradability

No data available Bioaccumulative potential

## Product:

Partition coefficient: n- octanol/water <u>Components:</u> propan-2-ol:	: Remarks: No data available
Partition coefficient: n- octanol/water butane :	: log Pow: 0.05
Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Additional ecological information	: No data available

# SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>Do not dispose of waste into sewer.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Dispose of in accordance with local regulations.</li> </ul>
Contaminated packaging	<ul> <li>Empty remaining contents.</li> <li>Dispose of as unused product.</li> <li>Do not re-use empty containers.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

Version 2.3

Revision Date 10/01/2023

Print Date 05/16/2024

#### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

#### The components of this product are reported in the following inventories:

DSLAll components of this product are on the Canadian DSLTSCAOn TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

#### SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Version 2.3	Revision Date 10/01/2023	Print Date 05/16/2024
Hazard pictograms	Flame Gas cylinder Exclamation mark	
Signal w ord Hazard statements	Danger:     Extremely flammable aerosol. Contains gas under press Causes serious eye irritation. May cause drowsiness or c	
Precautionary statements	<ul> <li>Prevention: Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a w ell-ventilated area. Wear eye protection/face protection.</li> <li>Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unw ell. IF IN EYES: Rinse cautiously with waterfor several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.</li> <li>Storage: Store in a w ell-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.</li> <li>Disposal: Dispose of contents/container in accordance with local regulation.</li> </ul>	

Version:	2.3
Revision Date:	10/01/2023
Print Date:	05/16/2024

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.