Version 2.1 Revision Date 10/01/2023 Print Date 04/26/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	MISTY CITRUS ALL PURPOSE CLEANER
Material number	:	00000000001001583
Manufacturer or supplier's	deta	ails
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	Compliance Services - 877-428-9937

Emergency telephone numbers			
For SDS Information	:	Compliance Services - 877-428-9937	
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded	
For a Transportation Emergency	:	CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616	

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	like fruit

GHS Classific	ation
----------------------	-------

Gases under pressure Eye irritation	: Liquefied gas : Category 2A
GHS label elements	
Hazard pictograms	: Gas cylinder Exclamation mark
Signal word	: Warning
Hazard statements	: H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation.
Precautionary statements	 Prevention: P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

Version 2.1

Revision Date 10/01/2023

Print Date 04/26/2024

easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. **Storage:** P410 + P403 Protect from sunlight. Store in a well-ventilated place.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 1 - < 3
Alcohols, C9-11, ethoxylated	68439-46-3	>= 1 - < 3
1-propoxypropan-2-ol	1569-01-3	>= 1 - < 3
propane	74-98-6	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.	
If inhaled	 If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. 	
In case of skin contact	 If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes. 	
In case of eye contact	 Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes. 	
If swallowed	 Clean mouth with water and drink afterwards plenty of water. Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. 	
Most important symptoms and effects, both acute and delayed	: Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed.	

Version 2.1	Revision Date 10/01/2023	Print Date 04/26/2024		
	Symptoms may include irritation, redness, pain, and rash. Causes serious eye irritation. Review section 2 of SDS to see all potential hazards.			
Notes to physician	: Treat symptomatically. Symptoms	s may be delayed.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Dry chemical Water Carbon dioxide (CO2) Foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Version 2.1		Revision Date 10/01/2023	Print Date 04/26/2024
Advice on safe handling	:	 Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist. 	
Conditions for safe storage	:	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards. No smoking. 	
Materials to avoid	:	Strong oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

Components with workplace control parameters

Engineering measures :

: effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Version 2.1	Revision Date 10/01/2023	Print Date 04/26/2024
Material Remarks	Protective glovesThe suitability for a specific workp with the producers of the protective	
Eye protection	: Access to clean water to rinse ey include: eye wash stations or sho with pure water. Tightly fitting safety goggles	· · ·
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous s	•
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and a	ut the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	white
Odour	:	like fruit
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	
		Not applicable
Evaporation rate	:	> 1 n-Butyl Acetate = 1.0
Flammability (solid, gas, liquid)	:	The product is not flammable.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	1 g/cm3
Solubility(ies)		
Water solubility	:	soluble
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	No data available
Viscosity		

Version 2.1	Revision Date 10/01/2023	Print Date 04/26/2024
Viscosity, kinematic	: No data available	
Heat of combustion	: 3.90 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition Symptoms of Overexposure	 None known. Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Causes serious eye irritation. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Version 2.1	Revision Date 10/01/2023	Print Date 04/26/2024
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
Components:		
Alcohols, C9-11, ethoxylated Acute oral toxicity		
Skin corrosion/irritation		
Product:		
Remarks: May irritate skin.		
Serious eye damage/eye irritation	1	
Product:		
Remarks: Severe eye irritation		
Respiratory or skin sensitisation		
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
Further information		
Product:		
Remarks: No data available		

Version 2.1

Revision Date 10/01/2023

Print Date 04/26/2024

SECTION 12. ECOLOGICAL INFORMATION	
Ecotoxicity	
No data available	
Persistence and degradability	
No data available Bioaccumulative potential	
Product:	
Partition coefficient: n- : octanol/water <u>Components:</u> butane :	Remarks: No data available
Partition coefficient: n- : octanol/water	Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	
No data available <u> Product:</u>	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological : information	No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Dispose of in accordance with local regulations.
	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

Version 2.1

Revision Date 10/01/2023

Print Date 04/26/2024

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.		Calculated product RQ
		(lbs)	(lbs)
2.2'-iminodiethanol	111-42-2	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Gases under pressure Serious eye damage or eye irritation
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Version 2.1

Revision Date 10/01/2023

Print Date 04/26/2024

California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSLAll components of this product are on the Canadian DSLTSCAOn TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 2.1

Revision Date 10/01/2023

Print Date 04/26/2024

Further information

NFPA:



0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic



Gas cylinder

Signal word Hazard statements Precautionary statements

Warning: Contains gas under pressure; may explode if heated. Causes serious eye irritation.

Prevention: Wash skin thoroughly after handling. Wear eye protection/face protection. Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage: Protect from sunlight. Store in a well-ventilated place.

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/26/2024

Exclamation mark

Version 2.1

Revision Date 10/01/2023

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.