

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ARMOR ALL PROFESSIONAL CLEAR COAT POLISH
YELLOW BUBBLE GUM

Material number : 00000000030001331

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : 404-352-1680

Emergency telephone numbers

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| | |
|------------|------------|
| Appearance | liquid |
| Colour | dark amber |
| Odour | aromatic |

GHS Classification

Flammable liquids : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Health hazard

Corrosion

Signal word : Danger

Hazard statements : H227 Combustible liquid.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|--|------------|-------------------|
| 2-butoxyethanol | 111-76-2 | >= 10 - < 30 |
| Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides | 61789-77-3 | >= 1 - < 5 |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | >= 1 - < 5 |
| Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides | 61791-10-4 | >= 1 - < 5 |
| propan-2-ol | 67-63-0 | >= 1 - < 5 |

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

| | | |
|--------------|----------|------------------|
| benzaldehyde | 100-52-7 | $\geq 0.1 - < 1$ |
|--------------|----------|------------------|

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
Wash contaminated clothing before re-use.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Continue rinsing eyes during transport to hospital.
Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include blistering, irritation, burns, and pain.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye damage.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
Water spray

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

| | |
|---|---|
| | Foam |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon dioxide (CO ₂) Carbon monoxide Smoke Nitrogen oxides (NO _x) |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Material can create slippery conditions. |
| Environmental precautions | : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities. |
| Methods and materials for containment and cleaning up | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

| | |
|-------------------------|--|
| Advice on safe handling | : Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. |
|-------------------------|--|

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Do not breathe vapours or spray mist.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-----------------|----------|----------------------------------|--|-----------|
| 2-butoxyethanol | 111-76-2 | TWA | 20 ppm | ACGIH |
| | | TWA | 5 ppm 24 mg/m ³ | NIOSH REL |
| | | TWA | 50 ppm 240 mg/m ³ | OSHA Z-1 |
| | | TWA | 25 ppm 120 mg/m ³ | OSHA P0 |
| | | PEL | 20 ppm 97 mg/m ³ | CAL PEL |
| propan-2-ol | 67-63-0 | TWA | 200 ppm | ACGIH |
| | | STEL | 400 ppm | ACGIH |
| | | TWA | 400 ppm 980 mg/m ³ | NIOSH REL |
| | | ST | 500 ppm 1,225 mg/m ³ | NIOSH REL |
| | | TWA | 400 ppm 980 mg/m ³ | OSHA Z-1 |
| | | TWA | 400 ppm 980 mg/m ³ | OSHA P0 |
| | | STEL | 500 ppm 1,225 mg/m ³ | OSHA P0 |
| | | PEL | 400 ppm 980 mg/m ³ | CAL PEL |
| benzaldehyde | 100-52-7 | STEL | 500 ppm 1,225 mg/m ³ | CAL PEL |
| | | TWA | 2 ppm | US WEEL |
| | | STEL | 4 ppm | US WEEL |

Biological occupational exposure limits

| Component | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-----------|---------|--------------------|---------------------|---------------|---------------------------|-------|
|-----------|---------|--------------------|---------------------|---------------|---------------------------|-------|

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

| | | | | | | |
|-----------------|----------|-------------------------|-------|--|---------------------|-----------|
| 2-BUTOXYETHANOL | 111-76-2 | Butoxyacetic acid (BAA) | Urine | End of shift (As soon as possible after exposure ceases) | 200.mg/g Creatinine | ACGIH BEI |
| PROPAN-2-OL | 67-63-0 | Acetone | Urine | End of shift at end of workweek | 40 mg/l | ACGIH BEI |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : dark amber

Odour : aromatic

Odour Threshold : No data available

pH : 7 - 8

Melting point/freezing point : No data available

Boiling point : > 100 °C

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

| | |
|--|-------------------------------|
| Flash point | : 66 °C Method: closed cup |
| Evaporation rate | : No data available |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density | : No data available |
| Relative density | : 1.004 |
| Density | : No data available |
| Solubility(ies) | |
| Water solubility | : No data available |
| Solubility in other solvents | : Not applicable |
| Partition coefficient: n- octanol/water | : No data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, kinematic | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. No decomposition if stored and applied as directed. |
| Conditions to avoid | : Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Incompatible materials | : Oxidizing agents |
| Hazardous decomposition products | : Carbon dioxide (CO ₂) Carbon monoxide Nitrogen oxides (NO _x) |

SECTION 11. TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include blistering, irritation, burns, and pain.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye damage.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

OSHA

2-butoxyethanol 111-76-2
No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 3,597 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 110 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg
Method: Calculation method

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

Components:

benzaldehyde:

Classification: May cause sensitisation by inhalation.

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

propan-2-ol :

Partition coefficient: n-octanol/water : log Pow: 0.05

benzaldehyde :

Partition coefficient: n-octanol/water : log Pow: 1.5

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):
UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (MIXED QUATERNARY AMMONIUM COMPOUNDS, MIXED QUATERNARY AMMONIUM COMPOUNDS), 9, III

Transportation Regulation: IATA (Cargo Air):
UN3082, Environmentally hazardous substance, liquid, n.o.s., (MIXED QUATERNARY AMMONIUM COMPOUNDS), 9, III

Transportation Regulation: IATA (Passenger Air):
UN3082, Environmentally hazardous substance, liquid, n.o.s., (MIXED QUATERNARY AMMONIUM COMPOUNDS), 9, III

Transportation Regulation: TDG (Canada):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------------|----------|--------------------|-----------------------------|
| 2,2'-iminodiethanol | 111-42-2 | 100 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|--------------|---------|--------------------|-----------------------------|
| formaldehyde | 50-00-0 | 100 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

- SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation
- SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:
- | | | |
|-----------------|----------|------|
| 2-butoxyethanol | 111-76-2 | 10 % |
|-----------------|----------|------|

California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, dichloroacetic acid, which is/are known to the State of California to cause cancer, and dichloroacetic acid, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

- DSL** This product contains one or more components that are listed on the Canadian NDSL. All other components are on the Canadian DSL.
- TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

Further information

NFPA:

| | |
|------------------------|----------|
| HEALTH | 3 |
| FLAMMABILITY | 2 |
| INSTABILITY | 0 |
| SPECIAL HAZARD. | |

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme


HMIS III:

| | |
|------------------------|-----------|
| HEALTH | 3* |
| FLAMMABILITY | 2 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Health hazard

Corrosion

Signal word

: **Danger:**

Hazard statements

: Combustible liquid. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection. Wear respiratory protection.

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs:

SAFETY DATA SHEET

ARMOR ALL PROFESSIONAL CLEAR COAT POLISH YELLOW BUBBLE GUM

Version 3.4

Revision Date 04/21/2020

Print Date 05/30/2020

Get medical advice/ attention. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local regulation.

| | |
|----------------|------------|
| Version: | 3.4 |
| Revision Date: | 04/21/2020 |
| Print Date: | 05/30/2020 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.