

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Material number : 00000000030001893

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : 404-352-1680

#### Emergency telephone numbers

**For SDS Information** : Compliance Services 1-877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	brown
Odour	characteristic

#### GHS Classification

Flammable liquids : Category 4  
Skin corrosion : Category 1B  
Serious eye damage : Category 1  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.  
H304 May be fatal if swallowed and enters airways.  
H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 Store in a well-ventilated place.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 10 - < 30
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	61789-77-3	>= 5 - < 10
2-butoxyethanol	111-76-2	>= 5 - < 10
Amines, tallow alkyl, ethoxylated	61791-26-2	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
diethyl phthalate	84-66-2	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

## SAFETY DATA SHEET

# ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

- Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.  
Wash off immediately with plenty of water for at least 15 minutes.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
Rinse immediately with plenty of water for at least 15 minutes.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include blistering, irritation, burns, and pain.  
Aspiration may cause pulmonary oedema and pneumonitis.  
Effects are dependent on exposure (dose, concentration, contact time).  
Causes severe skin burns and eye damage.  
May be fatal if swallowed and enters airways.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry chemical  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Water spray
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

Hazardous combustion products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide Smoke Nitrogen oxides (NO <sub>x</sub> )
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours or spray mist. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

Observe label precautions.  
Electrical installations / working materials must comply with  
the technological safety standards.

Materials to avoid : Oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 240 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm 120 mg/m <sup>3</sup>	OSHA P0
		PEL	20 ppm 97 mg/m <sup>3</sup>	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m <sup>3</sup>	NIOSH REL
		ST	500 ppm 1,225 mg/m <sup>3</sup>	NIOSH REL
		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA P0
		STEL	500 ppm 1,225 mg/m <sup>3</sup>	OSHA P0
		PEL	400 ppm 980 mg/m <sup>3</sup>	CAL PEL
		STEL	500 ppm 1,225 mg/m <sup>3</sup>	CAL PEL
diethyl phthalate	84-66-2	TWA	5 mg/m <sup>3</sup>	ACGIH
		TWA	5 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA P0
		PEL	5 mg/m <sup>3</sup>	CAL PEL

#### Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure	200.mg/g Creatinine	ACGIH BEI

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

PROPAN-2-OL	67-63-0	Acetone	Urine	ceases) End of shift at end of workwee k	40 mg/l	ACGIH BEI
-------------	---------	---------	-------	---	---------	-----------

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid

Colour

: brown

Odour

: characteristic

Odour Threshold

: No data available

pH

: 7.5 - 9.5

Melting point/freezing point

: No data available

Boiling point

: > 100 °C

Flash point

: 66 °C

Method: closed cup

Evaporation rate

: No data available

Upper explosion limit

: No data available

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 0.96
Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: Not applicable
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Aspiration may cause pulmonary oedema and pneumonitis. Effects are dependent on exposure (dose, concentration, contact time). Causes severe skin burns and eye damage. May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards.

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

Treat symptomatically. Symptoms may be delayed.

### Carcinogenicity:

#### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### ACGIH

Confirmed animal carcinogen with unknown relevance to humans

#### OSHA

2-butoxyethanol 111-76-2  
No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Acute toxicity

#### Product:

Acute oral toxicity : Acute toxicity estimate : 4,932 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 103.77 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

#### Components:

##### **2-butoxyethanol:**

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

##### **propan-2-ol:**

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg  
Method: Calculation method

##### **diethyl phthalate:**

Acute oral toxicity : LD50 Oral Rat: 8,600 mg/kg



# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

Acute inhalation toxicity : LC50 Rat: > 4,640 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal Rat, male and female: > 10,000 mg/kg

### Skin corrosion/irritation

**Product:**

Remarks: Extremely corrosive and destructive to tissue.

### Serious eye damage/eye irritation

**Product:**

Remarks: May cause irreversible eye damage.

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

**Product:**

Remarks: No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

#### Components:

**propan-2-ol :**  
Partition coefficient: n-octanol/water : log Pow: 0.05

**diethyl phthalate :**  
Partition coefficient: n-octanol/water : log Pow: 2.2 (41 °C)

### Mobility in soil

No data available

### Other adverse effects

No data available

#### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):  
UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (MIXED QUATERNARY AMMONIUM COMPOUNDS), 9, III, MP: (MIXED QUATERNARY AMMONIUM COMPOUNDS)

Transportation Regulation: IATA (Cargo Air):  
UN3082, Environmentally hazardous substance, liquid, n.o.s., (MIXED QUATERNARY AMMONIUM COMPOUNDS), 9, III

Transportation Regulation: IATA (Passenger Air):  
UN3082, Environmentally hazardous substance, liquid, n.o.s., (MIXED QUATERNARY AMMONIUM COMPOUNDS), 9, III

Transportation Regulation: TDG (Canada):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
diethyl phthalate	84-66-2	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

- SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Aspiration hazard
- SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:  
2-butoxyethanol 111-76-2 6 %

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### The components of this product are reported in the following inventories:

- DSL** This product contains one or more components that are listed on the Canadian NDSL. All other components are on the Canadian DSL.
- TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

---

## SECTION 16. OTHER INFORMATION

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

### Further information

#### NFPA:

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>INSTABILITY</b>	<b>0</b>
<b>SPECIAL HAZARD.</b>	

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme


#### HMIS III:

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms



Health hazard

Corrosion

Signal word

: **Danger:**

Hazard statements

: Combustible liquid. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage.

Precautionary statements

:

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. In case of fire: Use dry

# SAFETY DATA SHEET

## ARMOR ALL PROFESSIONAL VELOCITY CLEAR COAT PROTECTANT

Version 2.4

Revision Date 04/09/2020

Print Date 06/06/2020

sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place.

**Disposal:** Dispose of contents/container in accordance with local regulation.

---

Version:	2.4
Revision Date:	04/09/2020
Print Date:	06/06/2020

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.