Version 2.1		Revision Date 10/01/2023	Print Date 04/20/2024
SECTION 1. PRODUCT AN	D COMPA		
Material name	:	ZEP RESCUE CARPET SPOTTER 12CT	R NEXT STEP 20N18
Material number	:	000000000000000000000000000000000000000	
Manufacturer or suppl	ier's deta	ils	
Company	:	Zep Inc.	
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137	1

: Compliance Services - 877-428-9937

Compliance Services - 877-428-9937

877-541-2016 Toll Free - All Calls Recorded

CHEMTREC: 800-424-9300 - All Calls Recorded.

 Emergency
 In the District of Columbia 202-483-7616

:

:

:

Recommended use of the chemical and restrictions on use

#### SECTION 2. HAZARDS IDENTIFICATION

Emergency telephone numbers

#### **Emergency Overview**

For SDS Information

For a Transportation

For a Medical Emergency

Telephone

Appearance	Aerosol containing a liquefied gas			
Colour	colourless			
Odour	characteristic			

#### **GHS Classification**

Flammable aerosols Gases under pressure Eye irritation Reproductive toxicity	: Category 2 : Liquefied gas : Category 2A : Category 1B
GHS label elements	
Hazard pictograms	Flame Gas cylinder Health hazard Exclamation mark
Signal word	: Danger
Hazard statements	<ul> <li>H223 Flammable aerosol.</li> <li>H280 Contains gas under pressure; may explode if heated.</li> <li>H319 Causes serious eye irritation.</li> <li>H360 May damage fertility or the unborn child.</li> </ul>
Precautionary statements	: Prevention:

Version 2.1	Revision Date 10/01/2023	Print Date 04/20/2024
	<ul> <li>P201 Obtain special instructions</li> <li>P202 Do not handle until all safe and understood.</li> <li>P210 Keep away from heat, hot and other ignition sources. No sr</li> <li>P211 Do not spray on an open fl</li> <li>P251 Pressurized container: Do use.</li> <li>P264 Wash skin thoroughly after</li> <li>P280 Wear protective gloves/ proprotection/ face protection.</li> <li><b>Response:</b></li> <li>P305 + P351 + P338 IF IN EYES for several minutes. Remove cor easy to do. Continue rinsing.</li> <li>P308 + P313 IF exposed or condattention.</li> <li>P337 + P313 If eye irritation persentention.</li> <li><b>Storage:</b></li> <li>P410 + P412 Protect from sunlig temperatures exceeding 50 °C/ ~</li> <li><b>Disposal:</b></li> <li>P501 Dispose of contents/contair regulation.</li> </ul>	ty precautions have been read surfaces, sparks, open flames moking. ame or other ignition source. not pierce or burn, even after handling. otective clothing/ eye S: Rinse cautiously with water ntact lenses, if present and cerned: Get medical advice/ sists: Get medical advice/ sists: Get medical advice/ ht. Do not expose to 122 °F.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

CAS-No.	Concentration [%]
111-76-2	>= 5 - < 10
106-97-8	>= 3 - < 5
67-64-1	>= 3 - < 5
74-98-6	>= 1 - < 3
1303-96-4	>= 0.1 - < 1
7632-00-0	>= 0.1 - < 1
	111-76-2 106-97-8 67-64-1 74-98-6 1303-96-4

The exact percentages of disclosed substances are withheld as trade secrets.

### SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. Consult a physician after significant exposure.

Version 2.1	Revision Date 10/01/2023	Print Date 04/20/2024
In case of skin contact	<ul> <li>If skin irritation persists, call a Wash off immediately with ple minutes.</li> <li>If on clothes, remove clothes.</li> </ul>	enty of water for at least 15
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rin If eye irritation persists, consu Rinse immediately with plenty	
If swallowed	<ul> <li>Keep respiratory tract clear. Never give anything by mouth If symptoms persist, call a ph DO NOT induce vomiting unle physician or poison control ce Take victim immediately to he</li> </ul>	ysician. ess directed to do so by a enter.
Most important symptoms and effects, both acute and delayed	<ul> <li>Effects are immediate and de Effects are dependent on exp contact time).</li> <li>Symptoms may include irritat Chronic effects are delayed a observed during an exposure Causes serious eye irritation.</li> <li>May damage fertility or the ur Review section 2 of SDS to s</li> </ul>	bosure (dose, concentration, ion, redness, pain, and rash. and symptoms may not be nborn child.
Notes to physician	: Treat symptomatically. Symp	otoms may be delayed.

## SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet	
Unsuitable extinguishing media	High volume water jet	
Specific hazards during firefighting	Do not allow run-off from fire fighting to enter drains or w courses.	ater
Hazardous combustion products	Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	I
Further information	Collect contaminated fire extinguishing water separately. must not be discharged into drains. Fire residues and contaminated fire extinguishing water be disposed of in accordance with local regulations.	

Version 2.1	Revision Date 10/01/2023	Print Date 04/20/2024
	For safety reasons in case of fire, of separately in closed containments. Use a water spray to cool fully clos	
Special protective equipment for firefighters	: Wear self-contained breathing apprint necessary.	aratus for firefighting if

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling :	<ul> <li>Avoid exposure - obtain special instructions before use.</li> <li>Avoid contact with skin and eyes.</li> <li>For personal protection see section 8.</li> <li>Do not breathe vapours or spray mist.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Take precautionary measures against static discharges.</li> <li>Provide sufficient air exchange and/or exhaust in work rooms.</li> <li>Always replace cap after use.</li> <li>Dispose of rinse water in accordance with local and national regulations.</li> </ul>
Conditions for safe storage :	<ul> <li>BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.</li> <li>No smoking.</li> <li>Observe label precautions.</li> <li>Keep in a dry, cool and well-ventilated place.</li> <li>Electrical installations / working materials must comply with the technological safety standards.</li> </ul>
Materials to avoid :	Store and keep away from, oxidizing agents and acids.

Version 2.1

Revision Date 10/01/2023

Print Date 04/20/2024

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA PO
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
sodium borate, decahydrate	1303-96-4	TWA	5 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
		PEL	5 mg/m3	CAL PEL

### **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-BUTOXYETHANOL	111-76-2	Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI

ersion 2.1		Revision Date 1	0/01/2023		Print Date 04/2	20/2024
		acid (BAA)		shift (As soon as possible after exposure ceases)	Creatinine	
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BE
Engineering measures	; : (	effective ventilatio	on in all proc	essing area	IS	
Personal protective eq	uipment					
Respiratory protection	,	Use respiratory p ventilation is prov that exposures a	ided or expo	osure asses	sment demonst	trates
Hand protection						
Remarks		The suitability for with the producer				sed
Remarks	: /		rs of the prot	ective glove e eyes must	s. t be available, o	options
	: , ; ; ;	with the producer Access to clean v include: eye was with pure water.	rs of the prot water to rinse h stations or ing otection acco	ective glove e eyes must showers, o rding to the	s. t be available, o r eye wash bott amount and	options les

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: colourless
Odour	: characteristic
Odour Threshold	: No data available
рН	: 9-10
Melting point/freezing point	: No data available
Boiling point	: 43.3 °C
Flash point	: 43.3 °C

Version 2.1	Revision Date 10/01/2023	Print Date 04/20/2024
	Method: TCC	
Evaporation rate	: 1	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: not determined	
Relative vapour density	: No data available	
Density	: 0.9922 g/cm3	
Solubility(ies)		
Water solubility	: soluble in hot water, soluble in cold v	vater
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
reactions	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Acids Oxidizing agents
Hazardous decomposition products	: Carbon oxides

### SECTION 11. TOXICOLOGICAL INFORMATION

## **Potential Health Effects**

Aggravated	Medical	:	None known.
Condition			

Version 2.1	Revision Date 10/01/2023	Print Date 04/20/2024
Symptoms of Overexposure	<ul> <li>Effects are immediate and delayed Effects are dependent on exposure contact time).</li> <li>Symptoms may include irritation, re Chronic effects are delayed and sy observed during an exposure.</li> <li>Causes serious eye irritation.</li> <li>May damage fertility or the unborn Review section 2 of SDS to see all Treat symptomatically. Symptoms</li> </ul>	e (dose, concentration, edness, pain, and rash. ymptoms may not be child. potential hazards.
Carcinogenicity:		
IARC	Group 2A: Probably carcinogenic to h	
ACGIH	sodium nitrite Confirmed animal carcinogen with un humans	
OSHA	2-butoxyethanol No component of this product present	111-76-2 at levels greater than or
NTP	equal to 0.1% is on OSHA's list of reg No component of this product present equal to 0.1% is identified as a known by NTP.	ulated carcinogens. at levels greater than or
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 m Method: Calculation method	g/kg
Acute inhalation toxicity	: Acute toxicity estimate : 15.02 mg/ Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method	I
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 m Method: Calculation method	g/kg
Components:		
<b>2-butoxyethanol:</b> Acute oral toxicity	: LD50 Oral Rat: 880 mg/kg	
Acute dermal toxicity	: LD50 Dermal Rabbit: 1,060 mg/kg	
acetone: Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h	
	LC50 Rat: 50.1 mg/l	

SAFETY DATA SHEET **ZEP RESCUE CARPET SPOTTER NEXT STEP 20N18 12CT** Version 2.1 Revision Date 10/01/2023 Print Date 04/20/2024 Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg LD50 Rabbit: > 7,426 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation in susceptible persons. Serious eye damage/eye irritation Product: Remarks: Severe eye irritation Respiratory or skin sensitisation No data available Germ cell mutagenicity No data available Carcinogenicity No data available **Reproductive toxicity** No data available STOT - single exposure No data available STOT - repeated exposure No data available Aspiration toxicity

No data available

### **Further information**

Product:

Remarks: No data available

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

Version 2.1	Revision Date 10/01/2023	Print Date 04/20/2024
Persistence and degradability		
No data available Bioaccumulative potential		
Product:		
Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available	
Partition coefficient: n- octanol/water	: Pow: 2.89	
Mobility in soil		
No data available		
Other adverse effects		
No data available <u>Product:</u>		
Regulation	40 CFR Protection of Environment; Stratospheric Ozone - CAA Sectior Substances	
Remarks	This product neither contains, nor w with a Class I or Class II ODS as de Clean Air Act Section 602 (40 CFR + B).	efined by the U.S.
Additional ecological information	: No data available	

### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Dispose of in accordance with local regulations.</li> <li>The product should not be allowed to enter drains, water courses or the soil.</li> </ul>
Contaminated packaging	<ul> <li>Empty remaining contents.</li> <li>Dispose of as unused product.</li> <li>Do not re-use empty containers.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel):

Version 2.1

Revision Date 10/01/2023

Print Date 04/20/2024

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements: sodium nitrite 7632-00-0

### EPCRA - Emergency Planning and Community Right-to-Know Act

### **CERCLA** Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
sodium nitrite	7632-00-0	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, Gases under pressure Serious eye damage or eye irritation Reproductive toxicity	or solids)	
SARA 302	:	No chemicals in this material are subj requirements of SARA Title III, Section	•	ng
SARA 313	:	The following components are subject established by SARA Title III, Section 2-butoxyethanol	1 0	els 9.9865 %
California Prop. 65				

Version 2.1

Revision Date 10/01/2023

Print Date 04/20/2024

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### The components of this product are reported in the following inventories:

DSLAll components of this product are on the Canadian DSLTSCAOn TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 2.1

Revision Date 10/01/2023

Print Date 04/20/2024

### **Further information**

#### NFPA:



0 = not significant, 1 = Slight,

2 = Moderate, 3 = High


4 = Extreme

#### HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

- 2 = Moderate, 3 = High
- 4 = Extreme, \* = Chronic



Version 2.1

Revision Date 10/01/2023

Print Date 04/20/2024

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/20/2024

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.