Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP HD LOW PH PRESOAK XT-297

Material number : 0000000000757885

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers	-mergen	v telep	hone n	umbers
-----------------------------	---------	---------	--------	--------

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	amber, clear
Odour	characteristic

GHS Classification

Acute toxicity (Oral) : Category 3
Acute toxicity (Inhalation) : Category 3
Acute toxicity (Dermal) : Category 2
Skin corrosion : Category 1
Serious eye damage : Category 1

GHS label elements

Hazard pictograms :





Skull and crossbones

Signal word : Danger

Hazard statements : H301 + H331 Toxic if swallowed or if inhaled.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention**:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 + P202 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

SPECIAL HANDLING INSTRUCTIONS - Due to the unique hazards associated with hydrogen fluoride (HF), facilities need to have access to emergency showers, proper personal protective equipment (PPE), a supply of calcium gluconate gel, and complete training of all individuals on proper PPE and procedures.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P321 Specific treatment (see supplemental instructions on the administration of antidotes on this label).

SUPPLEMENTAL MEDICAL TREATMENT - Get immediate medical attention while applying and massaging in 2.5% calcium gluconate gel to the skin.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Benzenesulfonic acid, C10-16-alkyl derivs.	68584-22-5	>= 10 - < 20
hydrogen fluoride	7664-39-3	>= 5 - < 10
2-butoxyethanol	111-76-2	>= 3 - < 5

ZEP HD LOW PH PRESOAK XT-297

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

| sulphuric acid | 7664-93-9 | >= 3 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention while applying and massaging in 2.5% calcium gluconate gel. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get

immediate medical attention.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms of overexposure may include disorientation;

dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Symptoms may include blistering, irritation, burns, and pain.

Effects are immediate and delayed.

Fatal in contact with skin.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

Delayed treatment may result in hypoglycemia, begin treatment with topical application calcium gluconate, and

monitor blood chemistry.

Contact a poison treatment specialist immediately if large

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

quantities have been ingested or inhaled, or contact with large

portions of the body have occurred.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical

Water spray jet Carbon dioxide (CO2)

Alcohol-resistant foam

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Sulphur oxides

Smoke

Fluorine compounds

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

Technical measures : Due to the unique hazards associated with hydrogen fluoride

(HF), it is highly recommended that emergency pre-planning and training of employees occur to mitigate and facilitate rapid response to an exposure. Facilities need to have access to emergency showers, proper personal protective equipment (PPE), a supply of calcium gluconate gel, and complete training of all individuals on proper PPE and procedures.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Prevent unauthorized access.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

Store and keep away from bases and alkalies.

Store and keep away from bleach.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrogen fluoride	7664-39-3	TWA	0.5 ppm	ACGIH
		С	2 ppm	ACGIH
		TWA	3 ppm 2.5 mg/m3	NIOSH REL
		С	6 ppm 5 mg/m3	NIOSH REL
		TWA	3 ppm	OSHA Z-2
		TWA	3 ppm	OSHA P0
		STEL	6 ppm	OSHA P0
		TWA	0.5 ppm	ACGIH
		С	2 ppm	ACGIH
		TWA	3 ppm	OSHA P0
		STEL	6 ppm	OSHA P0
		PEL	0.4 ppm 0.33 mg/m3	CAL PEL
		STEL	1 ppm 0.83 mg/m3	CAL PEL

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
sulphuric acid	7664-93-9	TWA (Thoracic fraction)	0.2 mg/m3	ACGIH
		TWA	1 mg/m3	NIOSH REL
		TWA	1 mg/m3	OSHA Z-1
		TWA	1 mg/m3	OSHA P0
		PEL	0.1 mg/m3	CAL PEL
		STEL	3 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
HYDROFLUORIC ACID	7664-39-3	Fluoride	Urine	Prior to	2 mg/l	ACGIH BEI
				shift (16		
				hours		
				after		
				exposure		
				ceases)		
HYDROFLUORIC ACID		Fluoride	Urine	End of	3 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		
2-BUTOXYETHANOL	111-76-2	Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI
		acid (BAA)		shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

ZEP HD LOW PH PRESOAK XT-297

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling the

product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber, clear
Odour : characteristic
Odour Threshold : No data available

pH : < 1.0

Melting point/freezing point : No data available

Boiling point : 104.4 °C

Flash point

Not applicable

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 1.04 g/cm3

Solubility(ies)

Water solubility : soluble in cold water, soluble in hot water

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Bases

Hazardous decomposition

products

: Hydrogen fluoride Carbon oxides Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Symptoms may include blistering, irritation, burns, and pain.

Effects are immediate and delayed.

Fatal in contact with skin.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed. Delayed treatment may result in hypoglycemia, begin treatment with topical application calcium gluconate, and

monitor blood chemistry.

Contact a poison treatment specialist immediately if large quantities have been ingested or inhaled, or contact with large

portions of the body have occurred.

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

sulphuric acid 7664-93-9

ACGIH Suspected human carcinogen

ZEP HD LOW PH PRESOAK XT-297

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

sulphuric acid 7664-93-9

Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

sulphuric acid 7664-93-9

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 95.96 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 9.58 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 98.84 mg/kg

Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

Skin corrosion/irritation

Product:

Remarks: Causes skin burns. Harmful if absorbed through the skin. Contact results in immediate skin absorption which may cause hypocalcemia (calcium loss). This effect may be delayed for several hours after exposure. Severe over-exposure by absorption can result in death. Get immediate medical attention.

Components:

hydrogen fluoride:

Remarks: Causes skin burns. Harmful if absorbed through the skin. Contact results in immediate skin absorption which may cause hypocalcemia (calcium loss). This effect may be delayed for several hours after exposure. Severe over-exposure by absorption can result in death. Get immediate medical attention.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

ZEP HD LOW PH PRESOAK XT-297

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

ZEP HD LOW PH PRESOAK XT-297

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN2922, Corrosive liquids, toxic, n.o.s., (SULFURIC ACID, HYDROFLUORIC ACID), 8, (6.1), II

Transportation Regulation: IMDG (Vessel):

UN2922, CORROSIVE LIQUID, TOXIC, N.O.S., (SULFURIC ACID, HYDROFLUORIC ACID), 8, (6.1), II

Transportation Regulation: IATA (Cargo Air):

UN2922, Corrosive liquid, toxic, n.o.s., (SULFURIC ACID, HYDROFLUORIC ACID), 8, (6.1), II

Transportation Regulation: IATA (Passenger Air):

UN2922, Corrosive liquid, toxic, n.o.s., (SULFURIC ACID, HYDROFLUORIC ACID), 8, (6.1), II

Transportation Regulation: TDG (Canada):

UN2922, CORROSIVE LIQUID, TOXIC, N.O.S., (SULFURIC ACID, HYDROFLUORIC ACID), 8, (6.1), II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
hydrogen fluoride	7664-39-3	100	1984

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
hydrogen fluoride	7664-39-3	100	1984

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : The following components are subject to reporting levels

established by SARA Title III, Section 302:

hydrogen fluoride 7664-39-3 5.04 % sulphuric acid 7664-93-9 3.498 %

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

hydrogen fluoride 7664-39-3 5.04 % 2-butoxyethanol 111-76-2 4 %

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

Further information

NFPA:

HEALTH	3
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms





crossbones

Signal word

Hazard statements

Toxic if sw allowed or if inhaled. Fatal in contact with skin. Causes severe skin burns and eye damage.

Precautionary statements

Prevention: Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. SPECIAL HANDLING INSTRUCTIONS - Due to the unique hazards associated with hydrogen fluoride (HF), facilities need to have access to emergency showers, proper personal protective equipment (PPE), a supply of calcium gluconate gel, and complete training of all individuals on proper PPE and procedures.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair):

SAFETY DATA SHEET ZEP HD LOW PH PRESOAK XT-297

Version 3.1 Revision Date 10/01/2023 Print Date 03/29/2024

Take off immediately all contaminated clothing. Rinse skin w ith w ater. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously w ith water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Specific treatment (see supplemental instructions on the administration of antidotes on this label). SUPPLEMENTAL MEDICAL TREATMENT - Get immediate medical attention w hile applying and massaging in 2.5% calcium gluconate gel to the skin.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	03/29/2024

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.