Version 5.1	Revision Date 10/01/2023	Print Date 04/26/2024
SECTION 1. PRODUCT AN	ND COMPANY IDENTIFICATION	

Material name	:	ZEP FOAMING WALL CLEANER
Material number	:	ZUFWC18
Manufacturer or supplier's o	deta	ils
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	Compliance Services - 877-428-9937

Emergency telephone numbers			
For SDS Information	:	Compliance Services - 877-428-9937	
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded	
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.	
Emergency		In the District of Columbia 202-483-7616	

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

GHS Classification

Appearance	Aerosol containing a liquefied gas
Colour	off-white, opaque
Odour	ammoniacal

Gases under pressure	: Liquefied gas
GHS label elements	
Hazard pictograms	: Gas cylinder
Signal word	: Warning
Hazard statements	: H280 Contains gas under pressure; may explode if heated.
Precautionary statements	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 Pressurized container: Do not pierce or burn, even after use. Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place. P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

Version 5.1

Revision Date 10/01/2023

Print Date 04/26/2024

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 1 - < 5
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
1-butoxypropan-2-ol	5131-66-8	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
sodium nitrite	7632-00-0	>= 0.1 - < 1
The survey of the survey of the state of the survey	والمعرفة والمالية والمتعادية والمعالم والمعالية و	

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	:	Do not leave the victim unattended. Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
lf inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Immediately flush eye(s) with plenty of water.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Effects may be delayed, symptoms may include minor eye or skin irritation. Overexposure may cause mild eye or skin irritation.
Notes to physician	:	Treat symptomatically. Symptoms may be delayed.

Version 5.1

Revision Date 10/01/2023

Print Date 04/26/2024

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Do not allow run-off from fire fighting to enter drains or water courses.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid contact with skin and eyes.
	For personal protection see section 8.
	Smoking, eating and drinking should be prohibited in the
	application area.
	Take precautionary measures against static discharges.
	Provide sufficient air exchange and/or exhaust in work rooms.
	Dispose of rinse water in accordance with local and national

Version 5.1	Revision Date 10/01/2023	Print Date 04/26/2024
	regulations. Always replace cap after use. Do not breathe vapours or spray mi	st.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct su exposure and temperatures over 50 °C. Do not open by ford or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Keep in a dry, cool and well-ventilated place. 	
Materials to avoid	: Do not store near acids.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

Engineering measures	effective ventilation in all processing areas		
Personal protective equipme	ent		
Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.		
Hand protection Remarks	: The suitability for a specific workplace should be discussed		
	4 / 12		

Version 5.1	Revision Date 10/01/2023	Print Date 04/26/2024
	with the producers of the protective	e gloves.
Eye protection	: Access to clean water to rinse eye include: eye wash stations or show with pure water. Tightly fitting safety goggles	
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous su	
Hygiene measures	: Wash hands before breaks and at When using do not eat, drink or sm	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	off-white, opaque
Odour	:	ammoniacal
Odour Threshold	:	No data available
рН	:	10 - 11
Melting point/freezing point	:	No data available
Boiling point	:	101.67 °C
Flash point	:	
		Not applicable
Evaporation rate	:	1 n-Butyl Acetate = 1.0
Flammability (solid, gas, liquid)	:	The product is not flammable.
Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Vapour pressure	:	Not applicable
Relative vapour density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	soluble in hot water, soluble in cold water
Solubility in other solvents	:	not determined
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	No data available
Viscosity		

Version 5.1	Revision Date 10/01/2023	Print Date 04/26/2024
Viscosity, kinematic	: No data available	
Heat of combustion	: 4.30 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions Conditions to avoid	 No decomposition if stored and applied as directed. Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Acids
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects may be delayed, symptoms may include minor eye or skin irritation. Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:	
IARC	Group 2A: Probably carcinogenic to humans
ACGIH	sodium nitrite 7632-00-0 No component of this product present at levels greater than or
	equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Version 5.1	Revision Date 10/01/2023	Print Date 04/26/2024
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
Skin corrosion/irritation		
Product:		
Remarks: May cause skin irr	itation and/or dermatitis.	
Serious eye damage/eye irritat	ion	
Product:		
Remarks: May irritate eyes.		
Respiratory or skin sensitisatio	n	
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
Further information		
Product:		
Remarks: No data availab	le	

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Version 5.1	Revision Date 10/01/2023	Print Date 04/26/2024
Product:		
Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available	
Partition coefficient: n- octanol/water	: Pow: 2.89	
2-(2-butoxyethoxy)ethanol : Partition coefficient: n- octanol/water	: Pow: 1	
1-butoxypropan-2-ol : Partition coefficient: n- octanol/water	: Pow: 1.2	
Mobility in soil		
No data available		
Other adverse effects		
No data available Product:		
Regulation	40 CFR Protection of Environme Stratospheric Ozone - CAA Sec Substances	
Remarks	This product neither contains, no with a Class I or Class II ODS as Clean Air Act Section 602 (40 C + B).	s defined by the U.S.
Additional ecological information	: No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Version 5.1

Revision Date 10/01/2023

Print Date 04/26/2024

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements: sodium nitrite 7632-00-0

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Gases under pressure		
SARA 302	: No chemicals in this material are sub requirements of SARA Title III, Secti	•	rting
SARA 313	: The following components are subject to reporting levels established by SARA Title III, Section 313:		
	2-(2-butoxyethoxy)ethanol	112-34-5	2.3748 %
California Prop. 65			

This product does not contain any chemicals known to State of

Version 5.1

Revision Date 10/01/2023

Print Date 04/26/2024

California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSLAll components of this product are on the Canadian DSLTSCAOn TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 5.1

Revision Date 10/01/2023

Print Date 04/26/2024

Further information

NFPA:



0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	1
FLAMMABILITY	2
PHYSICAL HAZARD	2

0 = not significant, 1 =Slight,

- 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information: Hazard pictograms Gas cylinder Signal word Warning: Hazard statements Contains gas under pressure; may explode if heated. Precautionary statements Prevention: Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Storage: Protect from sunlight. Store in a well-ventilated place. Do not expose to

temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	5.1
Revision Date:	10/01/2023
Print Date:	04/26/2024

Version 5.1

Revision Date 10/01/2023

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.